



AperTO - Archivio Istituzionale Open Access dell'Università di Torino

Photocatalytic hydrogen production on Pt-loaded TiO2 inverse opals

This is the author's manuscript
Original Citation:
Availability:
This version is available http://hdl.handle.net/2318/154640 since 2019-02-04T12:38:59Z
Published version:
DOI:10.1016/j.apcatb.2014.08.028
Terms of use:
Open Access
Anyone can freely access the full text of works made available as "Open Access". Works made available under a Creative Commons license can be used according to the terms and conditions of said license. Use of all other works requires consent of the right holder (author or publisher) if not exempted from copyright protection by the applicable law.

(Article begins on next page)



UNIVERSITÀ DEGLI STUDI DI TORINO

2	
3 4 5 6 7 8	This Accepted Author Manuscript (AAM) is copyrighted and published by Elsevier. It is posted here by agreement between Elsevier and the University of Turin. Changes resulting from the publishing process - such as editing, corrections, structural formatting, and other quality control mechanisms - may not be reflected in this version of the text. The definitive version of the text was subsequently published in APPLIED CATALYSIS. B, ENVIRONMENTAL, 163 (2015), 452-458, DOI: 10.1016/j.apcatb.2014.08.028.
9 10 11	You may download, copy and otherwise use the AAM for non-commercial purposes provided that your license is limited by the following restrictions:
12 13 14	(1) You may use this AAM for non-commercial purposes only under the terms of the CC-BY-NC-ND license.
15 16	(2) The integrity of the work and identification of the author, copyright owner, and publisher must be preserved in any copy.
17 18 19	(3) You must attribute this AAM in the following format: Creative Commons BY-NC-ND license (<u>http://creativecommons.org/licenses/by-nc-nd/4.0/deed.en</u>), http://www.sciencedirect.com/science/article/pii/S0926337314005062

1	(revised manuscript)
2	
3	
4	Photocatalytic hydrogen production on Pt-loaded TiO ₂ inverse opals
5	
6	Fabrizio Sordello, Claudio Minero
7	Dipartimento di Chimica, Università di Torino, Via P: Giuria, 5, 10125 Torino, Italy.
8	
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	Corresponding authors:
21	e-mail: fabrizio.sordello@unito.it, claudio.minero@unito.it;
22	Fax: +39 011 670 5242; Tel: +39 011 670 5294 / 8449
23	

Abstract

TiO₂ inverse opals present increased photocatalytic production of H₂. TiO₂ inverse opals with 2 different pore size and TiO₂ macroporous structures with disordered arrangement of the pores have 3 been tested in the photocatalytic production of hydrogen in aqueous solution with a formate buffer 4 as hole scavenger. TiO₂ inverse opals belong to the family of metamaterials and exhibit unique 5 catalytic properties arising from their peculiar interaction with light. To discriminate the effects of 6 slow photons the hydrogen photoproduction, experiments were carried out at two different 7 wavelengths, at 365 nm where the effect of slow photons is maximized, and at 254 nm where it is 8 negligible. The resulting hydrogen production rates suggest a strong effect of the slow light and of 9 the polymer template used in the synthesis of the TiO₂ powders. The chemical properties of the 10 polymeric sacrificial template determine the crystalline phase of the sample and as a consequence 11 affect the catalytic performances of the resulting TiO₂ structures. 12

13

14

Keywords: TiO₂, inverse opal, hydrogen production, slow light, slow photons

16

Abbreviations: PBG: Photonic Band Gap; TIO: TiO₂ Inverse Opal; MP: macroporous; XRD: X-Ray
 Diffraction; PMMA: Polymethylmethacrylate; PS: Polystyrene

1. Introduction

Photonic crystals are materials in which the refractive index varies periodically in the space, and, 2 since light can be refracted and reflected at each interface, for a wavelength matching the lattice 3 periodicity there is the possibility to have constructive interference of the reflected waves. At that 4 wavelength light is completely reflected and cannot propagate inside the material because of the 5 presence of the photonic band gap (PBG) [1, 2]. Owing to this, photonic crystals find applications 6 as dielectric mirrors [3-6], waveguides [7], lasing cavities [8, 9], black body radiation modifiers 7 [10]. At the PBG edges light can propagate inside the photonic crystal, but its group velocity is 8 strongly reduced, and thus its interaction with the material increases, opening the field to a series of 9 diversified applications [11, 12]. 10

The increased light-matter interaction can be exploited in photocatalysis. Recently Tsai et al. 11 published an interesting report [13] on the interaction of light with hierarchical structured TiO₂, 12 specifically hollow spheres, which could harvest more light thanks to the scattering effect in the 13 microstructure while maintaining high surface area. Among photonic crystals TiO₂ inverse opals 14 (TIOs) have been studied extensively to improve the efficiency of the photocatalytic process [14-15 16]. TIOs are constituted of ordered arrays of holes in a TiO₂ matrix, but they only possess a partial 16 PBG, because the refractive index of TiO_2 is not high enough to open an omnidirectional gap [17]. 17 Previous results show that TIOs can significantly increment the photocatalytic performances of 18 TiO₂ thanks to the slow light phenomenon, which is the improved light-matter interaction due to the 19 reduction of the group velocity of light at the PBG edges [18-21]. In a previous work [21] we have 20 clarified that besides slow photons, porosity and specific surface area give only a negligible 21 contribute to the observed increase in photocatalytic activity of these structures. The 22 photoelectrochemical study of such materials [22] showed that TIOs and disordered macroporous 23 TiO₂ structures share the same recombination rate of the photogenerated charge carriers, but TIOs 24 are characterized by a faster electron transfer to the oxygen present in solution. After our early 25 analysis, other research works observed that the slow photons effect markedly improved the 26

photocatalytic activity in the oxidation of dyes [23], and increased three times the performance of
 Bi₂WO₆ deposited on SiO₂ photonic crystal compared to ordinary Bi₂WO₆ films [24]. The slow
 photon effect was also responsible for the enhanced photodegradation of the AO7 dye on TIOs
 doped with Ti³⁺ [25]. Conversely, the porous structure plays an important role in electrocatalytic
 reactions [26]. Thus the enhanced absorption of light, the improved reactivity towards oxygen and,
 to a lesser extent, the improved mass transfer of substrates make TIOs good candidates as catalysts
 for photo-reduction reactions.

To test the presence of a synergic effect between slow light and faster electron transfer to solution, in the present work we have compared the activity of Pt-loaded TIOs and of Pt-loaded macroporous disordered TiO₂ structures in hydrogen photoproduction experiments. To detect the effect of slow photons we performed irradiations at two different wavelengths: at 365 nm, where the TIOs synthesized can take advantage of slow light, and at 254 nm, where for the TIOs considered the slow light contribution to the photocatalytic activity is negligible. The hydrogen production rates of TIO samples are then compared with those of disordered macroporous samples.

15

16

17

2. Experimental

2.1. General

TiO₂ P25 was a gift of Degussa, methyl methacrylate (MMA, 99%), styrene (99%), 2,2'-azobis(2-18 methylpropionamidine) dihydrochloride (97%), titanium (IV) isopropoxide (97%), 19 hexachloroplatinic acid hexahydrate (37.5% Pt basis), formic acid (85% in water), ethanol (99.9%) 20 and ethylene dimethacrylate (98%), were purchased from Aldrich, sodium formate (99%) from 21 Merck. All the products were used without further purification. 22

23

24

2.2. Powders preparation

TIOs and TiO₂ macroporous structures were synthetized using different polymeric sacrificial templates. Polymethylmethacrylate (PMMA) and polystyrene (PS) templates were used to obtain TiO₂ structures with different pore sizes. The detailed synthesis procedure has been described elsewhere [21], here we only summarize the relevant issues. PMMA syntheses were carried out following a modified method proposed by Waterhouse and Waterland [27], in which the stirring procedure was changed [21]. With vigorous mechanical stirring well monodisperse colloids were produced, whereas with magnetic stirring polydisperse colloids were obtained.

Monodisperse polystyrene (PS) spheres were prepared with emulsion polymerization without emulsifier with a modified version of the method proposed by Goodwin et al.[28]. The size of the PS spheres produced is highly dependent on the composition of the synthesis mixture and on the reaction temperature, while the monodispersity of nanoparticles strongly depends on the stirring of the reaction mixture. To obtain well monodisperse colloids we carried out syntheses with mechanical stirring. Polystyrene polydisperse colloids were obtained mixing various batches of monodisperse colloids.

Polymer colloids size and their polydispersity were measured with an ALV-NIBS High Performance Particle Sizer (ALV GmbH). Polymeric colloidal suspensions were diluted approximately from 5 to 100-fold with Milli Q water before measurements and the particle size was extrapolated at infinite dilution.

Opals made with monodisperse polymer particles and polymeric disordered structures have been prepared loading PMMA or PS colloidal suspensions into 50 mL plastic falcon tubes followed by centrifugation (4300 rpm, 15°C for 90 min). The supernatant was then removed, and the polymeric disordered structure or the polymeric colloidal crystal was left to dry in air at 25°C for 24 hours.

²¹ Macroporous TiO₂ (MP) and TIOs were prepared filling the interstices among polymer spheres in ²² polymeric disordered structures and polymeric opals with a TiO₂ precursor. 1.5 g of the polymer ²³ template were gently crushed with a metal spatula to give fractured pieces of size <2 mm, which ²⁴ were then deposited on a filter paper (Whatman, Qualitative 1, 11µm) placed into a sintered glass ²⁵ filter funnel (Millipore). With a strong vacuum applied to the sintered glass filter funnel, a solution ²⁶ of TiO₂ precursor (4 mL titanium (IV) isopropoxide and 4 mL ethanol) was poured drop wise over the surface of the polymeric structure. Infiltrated samples were then left to dry in air at 25 °C for 2 h and recovered. Polymeric templates were then removed by means of calcination in air using the following protocol: the temperature was raised from 25 to 300°C at 2°C min⁻¹, held at 300°C for 5 h, then raised again from 300 to 550°C at 2°C min⁻¹, held at 550°C for 12 h. Samples were then finally allowed to cool to room temperature over 3–4 h.

On the as prepared materials, Pt was photocatalytically reduced adding H₂PtCl₆ to catalyst slurries
 and irradiating with UV light (see below).

8

9

2.3. X-ray powder diffraction

¹⁰ X-ray powder diffraction (XRD) patterns have been recorded with a PW3050/60 X'Pert PRO MPD ¹¹ diffractometer from PANalytical working in Bragg-Brentano configuration. The X-ray source was a ¹² high power ceramic tube PW3373/10 LFF with a Cu anode and the instrument was equipped with a ¹³ Ni filter to attenuate K_{β} . Diffracted photons were collected with a real time multiple strip ¹⁴ X'celerator detector. Powder samples have been hosted on SiO₂ amorphous sample holder.

The relative amounts of the different TiO₂ polymorphs were assessed with the method proposed by Zhang and Banfield [29].

17

18

2.4. Specific surface area

The specific surface area (SSA) of the powders synthesized was measured with nitrogen adsorption using an ASAP 2010 instrument (Micromeritics Instrument Corporation). Before the analysis all the samples were outgassed at 300°C in vacuum for 24 h. Specific surface area was calculated with the B.E.T. method [30], assuming an area of 0,162 nm² for the N₂ adsorbed molecule.

23

24

2.5. Hydrogen production

The hydrogen production experiments were carried out irradiating with UV light slurries containing 1 g L^{-1} of TiO₂ powder and 2 mg L^{-1} of Pt, added as H₂PtCl₆. The pH of the suspension was

buffered at 3.8 with the addition of a formic acid-sodium formate buffer 0.1 M. The formate buffer 1 acts also as hole scavenger. The irradiation experiments were carried out in magnetically stirred, 2 cylindrical quartz cells (3.5 cm inner diameter, 2 cm height), containing 5 mL of slurry. Before 3 irradiation the cell containing the slurry was carefully purged with nitrogen to remove oxygen from 4 the reaction environment. Hydrogen evolution was followed withdrawing periodically 2.5 ml of gas from the irradiation cell and replacing it with the same volume of N₂. The gas sample was analysed 6 with an Agilent 490 Micro GC gas chromatograph equipped with a Molsieve 5Å column. During 7 the analysis the column was kept at a temperature of 90°C and at a pressure of 200 kPa, the carrier 8 gas was argon. The total amount of H₂ produced as a function of time was calculated from the 9 concentration in the sampled gas, from the volume of gas in the irradiation cell and considering the 10 previous samplings. 11

To evaluate the effect of the slow photons the irradiations were performed at two different UV wavelengths (365 nm and 254 nm). The radiation source at 365 nm was a Philips PLS-10 lamp at a distance of 10 cm from the quartz cell with a flat Al foil as a reflector. The irradiance on top of the solutions was 78 W m⁻², measured with a CO.FO.ME.GRA. power meter. Irradiation at 254 nm was carried out with a 9 W Philips TUV PL-S lamp at a distance of 10 cm from the quartz cell, emitting 2.3 W in UVC. Fig. 1 reports the emission spectra of the two lamps, measured with an Ocean Optics SD2000 CCD.

19

20

2.6. Computational details

²¹ Photonic bands diagrams have been calculated with a freely available software [31].

22

23

24

3. Results and discussion

3.1. Powders characterization

In the present work five different samples have been studied. Among them two have been prepared
 starting from PMMA templates. Their AFM, SEM and optical spectra, as well as the photocatalytic

activity toward phenol oxidation have been investigated in a previous work [21]. Two samples have
 been obtained from PS templates, and, besides the optical and morphological characterization, on
 them an extensive photoelectrochemical study has been performed by means of voltammetry,
 potentiometry and electrochemical impedance spectroscopy [22]; the fifth sample was P25, here
 used as a reference for the activity of the synthesized samples.

The sample prepared using PMMA disordered structure as a template (macroporous disordered 6 structure, MP-PMMA) is a macroporous powder with disordered pore structure, and as a 7 consequence there is no PBG. Using PMMA ordered structure as a template, the inverse opal was 8 obtained (TIO-PMMA). The inverse opal TIO-PMMA has a pore structure with long range order. 9 During calcination the PMMA template shrinks considerably (up to 50%). Starting from PMMA 10 with particle diameter about 250 nm, the sample TIO-PMMA has pores with diameter around 125 11 nm (pseudo-PBG around 280 nm in air, 320-330 nm in water). Starting from PMMA with particle 12 diameter around 420-450 nm, the sample MP-PMMA has pores with a mean diameter around 220 13 nm [21]. 14

The TIO-PS sample, prepared from the PS opal powder, has an ordered arrangement of the pores, 15 each pore has a diameter of 250 nm and it is separated from its closest neighbours by 80 nm thick 16 TiO₂ walls. The corresponding opal template was composed of PS spheres with diameter of 360 17 nm, indicating a limited shrinkage with respect to PMMA. In this case the pseudo-PBG is located at 18 500 nm, but there are photonic bands characterised by low group velocity also at 330-380 nm [22]. 19 The sample MP-PS has a very similar pore size distribution, but its structure lacks in long range 20 order, and, as in the case of MP-PMMA, there is no PBG and no way to exploit the slow photon 21 effect [22]. 22

The pore size distributions and the specific surface areas (SSA) of the samples synthesized are summarized in Table 1. The powders obtained from PS templates have higher specific surface area with respect to PMMA templates. In addition the data of Table 1 suggest that the surface area increases with the pore size at the 3/2 power, opposite to the expected inverse dependence. As mentioned before PMMA templates shrink during calcination, and this process can cause the
 occlusion of part of the macropores, resulting in a reduced SSA. In the case of smaller macropores
 the channels connecting the macropores network are also smaller and easier to occlude.

X-ray powder diffractograms reported in Fig. 2 show that anatase is the dominant TiO₂ crystalline 4 phase when PMMA is used as sacrificial template, while rutile is present only as a trace (< 2%). 5 When PS is used as polymer template, the presence of rutile and brookite, in the sample TIO-PS, 6 becomes significant. MP-PS contains about 30% of rutile, while TIO-PS is composed of 57% 7 anatase, 36% brookite and 7% rutile. These relative amounts are only approximate, because it is not 8 possible to finely homogenize the samples without losing the properties arising from the 3D 9 structure of the powders. These differences in compositions can be explained in terms of the 10 chemical properties of the polymer templates. PMMA has a certain number of carboxylate groups, 11 and it is known that carboxylate can complex preferentially anatase {001} facets, changing the 12 growing rate ratio of {001} facets to {101} facets [32-35]. The diffractograms reported in Fig. 2 13 suggest also that the carboxylate groups can favour the nucleation of anatase rather than rutile or 14 brookite, since in the samples obtained using PMMA as template rutile and brookite are almost 15 absent. 16

17

18

3.2. Hydrogen production

The initial slurry contains the photocatalyst as a suspended solid, H₂PtCl₆ and the formate buffer. In 19 the first step of the irradiation, the photoelectrons produced by UV light reduce Pt(IV) to Pt(0), and 20 are responsible for the Pt photodeposition [36]. In this process the formate buffer has the function of 21 hole scavenger. Once the Pt is deposited and the suspension turned to a pale grey, the production of 22 hydrogen started. Fig. 3 reports the cumulative hydrogen produced as a function of the time. The 23 extrapolation of the trends when hydrogen production starts (intercept with the abscissa) shows that 24 at both 254 nm and 365 nm the hydrogen evolution begins even before the fifth minute of 25 irradiation. In some cases the hydrogen evolution seems to start at even negative times: this effect is 26

due to the non-linearity of hydrogen production in the very first minutes of irradiation, after which it follows a linear trend. The rates are reported in Fig.4, together with the rates normalized by the SSA.

From a general analysis of the plots in Fig. 3 and Fig. 4 it can be seen that at 254 nm the hydrogen production rates and the SSA normalized rates roughly double with respect to the rates observed at 365 nm. The comparison of the absolute rates at 254 nm and 365 nm is challenging because the intensity of the incident light is different, and other factors like the different absorption coefficient of TiO₂ at those wavelengths and the different scattering of light [37] are difficult to be estimated. Thus, only are the relative rates at each wavelength significant to assess the role of the material geometrical arrangement.

Considering the 365 nm irradiation using the TIO-PMMA and MP-PMMA samples (Fig. 4b) it can 11 be seen that the ordered three dimensional structure nearly doubles the surface normalized 12 photocatalytic activity of P25 and macroporous disordered specimen. The same observation can be 13 made for the powders obtained from PS templates, even if, in this case, TIO-PS is only 25% more 14 active than its macroporous homologue (Fig 4b). In general, both for the rate and the normalized 15 rate the performance is in the order MP < TIO. Since at those photon energies flat photonic bands in 16 the diagram frequency (ω) vs wavevector (k) are present for both TIO-PMMA and TIO-PS (Fig. 17 5), slow photons can reasonably be the cause of the observed differences in hydrogen production, 18 since, considering separately PMMA and PS derived samples, minor differences in surface 19 chemistry or crystallinity exist due to the same synthesis conditions. Thus, the major difference 20 among TIOs and their macroporous MP analogues is the 3D arrangement of the pores that 21 influences the ability to absorb the incident light. 22

At 254 nm (Fig. 4a), both for the rate and the normalized rate the performance follows the trend MP TIO. The surface normalized rate of the sample TIO-PMMA is very similar to that of MP-PMMA, and in the case of PS template samples MP-PS is definitely more active than TIO-PS. Considering the photonic band diagram of TIO-PS (Fig. 5) at 254 nm there are few photonic bands

characterized by a low group velocity. At those energies TiO_2 has a higher absorption coefficient [38], and the lengthening of the effective optical path due to slow photons is not crucial in increasing the absorbance.

Comparing now the rates of the samples focusing on the different chemical composition of the 4 templates (Fig. 4) it can be noticed that although the rates are comparable, the surface normalized 5 rates of PS samples are significantly lower with respect to PMMA samples both at 365 nm and 254 6 nm, because of the higher SSAs of the PS samples. The polymer template has an influence on the 7 crystalline phases present in the synthesized samples (Fig. 2) and also an effect on the surface 8 properties is very likely. Since photocatalytic properties depend on the TiO₂ crystalline phases and 9 on the surface exposed [39], the choice of the polymer template has an influence on the behaviour 10 of the material under irradiation. It has been demonstrated that the activity in hydrogen 11 photoproduction depends on the particle shape and on the facets exposed by the catalyst, and 12 anatase nanoparticles synthesized in the presence of carboxylic acids and exposing {001} facets are 13 very active [40, 41]. The fact that TiO₂ structures obtained from PMMA templates are, for the most 14 part, more active than those obtained with PS is in agreement with those results. Moreover, the 15 presence of rutile in the PS samples, characterized by a lower energy of the conduction band [42] 16 with respect to anatase, decreases the energy of the conduction band with respect to samples 17 obtained from PMMA, where almost only anatase is present (Table 1), and decreases the 18 overpotential available for the H₂ production, resulting in a lower activity. 19

We reported a higher reaction rate of photogenerated electrons with oxygen present in solution for the TIO-PS sample with respect to its MP-PS homologue, while the recombination rate of the photogenerated charge carriers was the same in both TIO-PS and MP-PS [22]. Following this evidence, we expected a faster hydrogen evolution from the TIO-PS sample by irradiation at 254 nm, where the effect of slow photons is negligible. A greater activity of TIOs at 254 nm would be the evidence of a faster electron transfer rate in TIOs with respect to macroporous analogues. On the contrary, we observed slightly lower activities for the TIOs compared to MP samples (Fig. 4a).

This is the evidence that the improvement in TIO activity at 365 nm is entirely due to the slow photon effect (Fig. 4b). This also suggests that the electron transfer to solution via the Pt co-catalyst on TIOs is by no means faster than for MP structures. The production of H₂ occurs on Pt sites with small overpotentials, and the rate determining step can be the electron transfer from the metal to H⁺ or water [43], or the catalytic desorption of H₂ from the Pt surface [44]. This situation is completely different from the dioxygen reduction on TiO₂, where the reduction occurs on adsorbed oxygen (surface traps) with high overpotentials [43].

8

9

4. Conclusions

Irradiation experiments performed at 254 nm show that TIOs and disordered MP structures obtained 10 from the same polymer template (PMMA or PS) have hydrogen production rate in the order MP 11 >TIO. Upon irradiation at 365 nm due to the slow light phenomenon the synthesized TiO_2 inverse 12 opals have hydrogen production rate (or SSA normalized rate) larger than disordered macroporous 13 structures that did not possess an ordered arrangement of the pores (MP <TIO). The increase in 14 activity is due to a better exploitation of the incident light. The rate of the synthesized TiO₂ powders 15 is also influenced by the chemical properties of the polymeric template, which determines not only 16 the pore size and the order of the pore structure, but also the TiO₂ crystalline phases. Nevertheless, 17 these and other factors such as the kinetics of the charge transfer at the interface, or the different 18 crystalline facets exposed [45], cannot account for the different orders of reactivity found at 19 different irradiation wavelengths, because the better exploitation of light is the cause of this 20 phenomenon, which is observed both for oxidation [20] and, in this work, for reduction reactions. 21 Owing to this, the strategy can be conveniently used in every photocatalytic reaction. 22

Acknowledgements

- ² The authors thank Dr. Giuliana Magnacca for her helpfulness and expertise in nitrogen adsorption
- experiments. The financial support from project PHOTORECARB Progetti di Ateneo/CSP 2012 -
- ⁴ Call 03 Università di Torino & Compagnia di S.Paolo is gratefully acknowledged.

- Table 1: Specific surface area, diameter of the macropores and TiO₂ crystalline phases
 - SSA (m² g⁻¹) Sample Crystalline phases Macropore size (nm) TIO-PMMA 18 125 Anatase, Rutile < 1% Anatase, Rutile ≈ 2% MP-PMMA 28 200-220 A ≈ 57%, B ≈ 36%, R ≈ 7% TIO-PS 74 330 MP-PS A ≈ 70%, R ≈ 30% 69 300-330 45 [46] A ≈ 80%, R ≈ 20% [47] P25 -
- ⁴ present in the TiO₂ powders synthesized (A: anatase, B: brookite, R: rutile)

2

5

6









5 Fig. 2



Fig. 3







5 Fig. 5

Table caption

- ² Table 1: Specific surface area, diameter of the macropores and TiO₂ crystalline phases present in
- the TiO₂ powders synthesized (A: anatase, B: brookite, R: rutile)

Figures captions

² Fig. 1 Emission spectra of a Philips TUV PL-S lamp (a) and of a Philips PLS-10 lamp (b).

⁴ Fig. 2 XRD patterns of (a) MP-PMMA, (b) TIO-PMMA, (c) MP-PS and (d) TIO-PS. The letter A ⁵ denotes anatase, B brookite and R rutile.

6

3

Fig. 3 Hydrogen produced as a function of the irradiation time for suspensions containing 1 g L^{-1} of different TiO₂ powders and 2 mg L^{-1} of Pt in the presence of formate buffer 0.1 M at pH 3.8. The radiation source had an emission maximum at 254 nm (a) and at 365 nm (b).

10

Fig. 4 Hydrogen production rates and surface normalized rates for powder samples irradiated at 254 nm (a) and at 365 nm (b). All samples were suspensions containing 1 g L^{-1} of different TiO₂ and 2 mg L^{-1} of Pt in the presence of formate buffer 0.1 M at pH 3.8.

14

Fig. 5 Calculated photonic band diagram for TIO powders in water with data of Table 1. The frequencies used during irradiation experiments are highlighted. For TiO₂ $\varepsilon_1 = 5.5$; for water $\varepsilon_1 =$ 1.7.

Research highlights

- ² 1- TiO₂ inverse opals and macroporous TiO₂ were used in H₂ production experiments
- ³ 2- Inverse opals show higher rates due to slow photons
- ⁴ 3- Polymer template influences the crystallinity and the performance of TiO₂ samples
- ⁵ 4- No evidence for faster electron transfer in TIOs during H₂ photoproduction
- ⁶ 5- Inverse opal are effective both on oxidation and reduction photocatalytic reactions

1 References

- ² [1] E. Yablonovitch, Photonic crystals: Semiconductors of light, Sci. Am., 285 (2001) 46-50.
- ³ [2] J.D. Joannopoulos, S.G. Johnson, J.N. Winn, R.D. Meade, Photonic Crystals
- ⁴ Molding the Flow of Light, second ed., Princeton University Press, Princeton, 2008.
- 5 [3] M. Ishii, M. Harada, A. Tsukigase, H. Nakamura, Three-dimensional structure analysis of opaline photonic crystals
- ⁶ by angle-resolved reflection spectroscopy, J. Opt. A-Pure Appl. Op., 9 (2007) S372-S376.
- [4] A. Mihi, M.E. Calvo, J.A. Anta, H. Miguez, Spectral response of opal-based dye-sensitized solar cells, J. Phys.
 ⁸ Chem. C, 112 (2008) 13-17.
- ⁹ [5] S. Nishimura, N. Abrams, B.A. Lewis, L.I. Halaoui, T.E. Mallouk, K.D. Benkstein, J. van de Lagemaat, A.J. Frank,
- Standing wave enhancement of red absorbance and photocurrent in dye-sensitized titanium dioxide photoelectrodes coupled to photonic crystals, J. Am. Chem. Soc., 125 (2003) 6306-6310.
- [6] P.G. O'Brien, N.P. Kherani, A. Chutinan, G.A. Ozin, S. John, S. Zukotynski, Silicon photovoltaics using conducting
 photonic crystal back-reflectors, Adv. Mater., 20 (2008) 1577-1582.
- [7] X. Letartre, C. Seassal, C. Grillet, P. Rojo-Romeo, P. Viktorovitch, M.L. d'Yerville, D. Cassagne, C. Jouanin, Group
- velocity and propagation losses measurement in a single-line photonic-crystal waveguide on InP membranes, Appl. Phys. Lett., 79 (2001) 2312-2314.
- [8] I.D.W. Samuel, G.A. Turnbull, Organic Semiconductor Lasers, Chem. Rev., 107 (2007) 1272-1295.
- [9] A. Mekis, M. Meier, A. Dodabalapur, R.E. Slusher, J.D. Joannopoulos, Lasing mechanism in two-dimensional photonic crystal lasers, Appl. Phys. A: Mater. Sci. Process., 69 (1999) 111-114.
- [10] M. Florescu, H. Lee, I. Puscasu, M. Pralle, L. Florescu, D.Z. Ting, J.P. Dowling, Improving solar cell efficiency using photonic band-gap materials, Sol. Energy Mater. Sol. Cells, 91 (2007) 1599-1610.
- [11] T. Baba, Slow light in photonic crystals, Nat. Photonics, 2 (2008) 465-473.
- [12] Y. Zhao, H.-W. Zhao, X.-Y. Zhang, B. Yuan, S. Zhang, New mechanisms of slow light and their applications, Opt.
 Laser Technol., 41 (2009) 517-525.
- ²⁵ [13] M.-C. Tsai, J.-Y. Lee, P.-C. Chen, Y.-W. Chang, Y.-C. Chang, M.-H. Yang, H.-T. Chiu, I.N. Lin, R.-K. Lee, C.-Y.
- Lee, Effects of size and shell thickness of TiO2 hierarchical hollow spheres on photocatalytic behavior: An experimental and theoretical study, Applied Catalysis B: Environmental, 147 (2014) 499-507.
- [14] M.M. Ren, R. Ravikrishna, K.T. Valsaraj, Photocatalytic degradation of gaseous organic species on photonic band-
- ²⁹ gap titania, Environ. Sci. Technol., 40 (2006) 7029-7033.
- ³⁰ [15] M. Srinivasan, T. White, Degradation of methylene blue by three-dimensionally ordered macroporous titania, ³¹ Environ. Sci. Technol., 41 (2007) 4405-4409.
- ³² [16] Q. Li, J.K. Shang, Inverse opal structure of nitrogen-doped titanium oxide with enhanced visible-light ³³ photocatalytic activity, J. Am. Ceram. Soc., 91 (2008) 660-663.
- [17] W.T. Dong, H.J. Bongard, F. Marlow, New type of inverse opals: Titania with skeleton structure, Chem. Mater., 15 (2003) 568-574.
- [18] F. Sordello, V. Maurino, C. Minero, Improved Photochemistry of TiO₂ Inverse Opals and Some Examples, in: D.S.
 Saha (Ed.) Molecular Photochemistry Various Aspects, InTech 2012, pp. 63-86.
- [19] J.I.L. Chen, E. Loso, N. Ebrahim, G.A. Ozin, Synergy of slow photon and chemically amplified photochemistry in platinum nanocluster-loaded inverse titania opals, J. Am. Chem. Soc., 130 (2008) 5420-5421.
- [20] J.I.L. Chen, G. vonFreymann, S.Y. Choi, V. Kitaev, G.A. Ozin, Amplified Photochemistry with Slow Photons,
 Adv. Mater., 18 (2006) 1915-1919.
- [21] F. Sordello, C. Duca, V. Maurino, C. Minero, Photocatalytic metamaterials: TiO₂ inverse opals, Chem. Commun.,
 47 (2011) 6147-6149.
- [22] F. Sordello, V. Maurino, C. Minero, Photoelectrochemical study of TiO_2 inverse opals, J. Mater. Chem., 21 (2011) 19144 - 19152.
- [23] M. Wu, J. Liu, J. Jin, C. Wang, S. Huang, Z. Deng, Y. Li, B.-L. Su, Probing significant light absorption
 enhancement of titania inverse opal films for highly exalted photocatalytic degradation of dye pollutants, Applied
 Catalysis B: Environmental, 150–151 (2014) 411-420.
- ⁴⁹ [24] S. Sun, W. Wang, L. Zhang, J. Xu, Bi₂WO₆/SiO₂ photonic crystal film with high photocatalytic activity under ⁵⁰ visible light irradiation, Applied Catalysis B: Environmental, 125 (2012) 144-148.
- [25] D. Qi, L. Lu, Z. Xi, L. Wang, J. Zhang, Enhanced photocatalytic performance of TiO2 based on synergistic effect of Ti3+ self-doping and slow light effect, Applied Catalysis B: Environmental, 160–161 (2014) 621-628.
- [26] S. Chai, G. Zhao, Y. Wang, Y.-n. Zhang, Y. Wang, Y. Jin, X. Huang, Fabrication and enhanced electrocatalytic
- activity of 3D highly ordered macroporous PbO₂ electrode for recalcitrant pollutant incineration, Applied Catalysis B:
 Environmental, 147 (2014) 275-286.
- ⁵⁶ [27] G.I.N. Waterhouse, M.R. Waterland, Opal and inverse opal photonic crystals: Fabrication and characterization, ⁵⁷ Polyhedron, 26 (2007) 356-368.
- [28] J.W. Goodwin, J. Hearn, C.C. Ho, R.H. Ottewill, Studies on the preparation and characterisation of monodisperse
- ⁵⁹ polystyrene laticee, Colloid Polym. Sci., 252 (1974) 464-471.

- [29] H. Zhang, J.F. Banfield, Understanding Polymorphic Phase Transformation Behavior during Growth of
 Nanocrystalline Aggregates: Insights from TiO2, J. Phys. Chem. B, 104 (2000) 3481-3487.
- [30] S. Brunauer, P.H. Emmett, E. Teller, Adsorption of Gases in Multimolecular Layers, J. Am. Chem. Soc., 60 (1938)
 309-319.
- [31] S.G. Johnson, J.D. Joannopoulos, Block-iterative frequency-domain methods for Maxwell's equations in a
 planewave basis, Opt. Express, 8 (2001) 173-190.
- [32] C.-T. Dinh, T.-D. Nguyen, F. Kleitz, T.-O. Do, Shape-Controlled Synthesis of Highly Crystalline Titania
 Nanocrystals, ACS Nano, 3 (2009) 3737-3743.
- [33] J. Joo, S.G. Kwon, T. Yu, M. Cho, J. Lee, J. Yoon, T. Hyeon, Large-Scale Synthesis of TiO₂ Nanorods via
 Nonhydrolytic Sol–Gel Ester Elimination Reaction and Their Application to Photocatalytic Inactivation of E. coli, J.
- ¹¹ Phys. Chem. B, 109 (2005) 15297-15302.
- [34] Y.-w. Jun, M.F. Casula, J.-H. Sim, S.Y. Kim, J. Cheon, A.P. Alivisatos, Surfactant-Assisted Elimination of a High
- Energy Facet as a Means of Controlling the Shapes of TiO₂ Nanocrystals, J. Am. Chem. Soc., 125 (2003) 15981-15985.
- [35] X.-L. Li, Q. Peng, J.-X. Yi, X. Wang, Y. Li, Near Monodisperse TiO₂ Nanoparticles and Nanorods, Chem. Eur. J., 12 (2006) 2383-2391.
- [36] B. Kraeutler, A.J. Bard, Heterogeneous photocatalytic preparation of supported catalysts. Photodeposition of platinum on titanium dioxide powder and other substrates, J. Am. Chem. Soc., 100 (1978) 4317-4318.
- ¹⁸ [37] C. Minero, D. Vione, A quantitative evalution of the photocatalytic performance of TiO₂ slurries, Applied ¹⁹ Catalysis B: Environmental, 67 (2006) 257-269.
- [38] G.E. Jellison, L.A. Boatner, J.D. Budai, B.S. Jeong, D.P. Norton, Spectroscopic ellipsometry of thin film and bulk anatase (TiO2), J. Appl. Phys., 93 (2003) 9537-9541.
- [39] W.Q. Fang, X.-Q. Gong, H.G. Yang, On the Unusual Properties of Anatase TiO₂ Exposed by Highly Reactive Facets, J. Phys. Chem. Lett., 2 (2011) 725-734.
- [40] H.J. Yun, H. Lee, J.B. Joo, N.D. Kim, J. Yi, Effect of TiO₂ Nanoparticle Shape on Hydrogen Evolution via Water Splitting, J. Nanosci. Nanotechnol., 11 (2011) 1688-1691.
- [41] T. Kimijima, T. Sasaki, M. Nakaya, K. Kanie, A. Muramatsu, Photocatalytic Activity of Ni-loaded TiO₂
 Nanoparticles Precisely Controlled in Size and Shape, Chem. Lett., 39 (2010) 1080-1081.
- [42] L. Kavan, M. Grätzel, S.E. Gilbert, C. Klemenz, H.J. Scheel, Electrochemical and Photoelectrochemical Investigation of Single-Crystal Anatase, J. Am. Chem. Soc., 118 (1996) 6716-6723.
- ³⁰ [43] Z. Kasarevic-Popovic, D. Behar, J. Rabani, Role of Excess Electrons in TiO2 Nanoparticles Coated with Pt in ³¹ Reduction Reactions Studied in Radiolysis of Aqueous Solutions, J. Phys. Chem. B, 108 (2004) 20291-20295.
- [44] R. Baba, S. Nakabayashi, A. Fujishima, K. Honda, Investigation of the mechanism of hydrogen evolution during
 photocatalytic water decomposition on metal-loaded semiconductor powders, J. Phys. Chem., 89 (1985) 1902-1905.
- ³⁴ [45] J. Yu, J. Low, W. Xiao, P. Zhou, M. Jaroniec, Enhanced Photocatalytic CO2-Reduction Activity of Anatase TiO₂ ³⁵ by Coexposed {001} and {101} Facets, J. Am. Chem. Soc., 136 (2014) 8839-8842.
- ³⁶ [46] J. Yu, J. Fan, B. Cheng, Dye-sensitized solar cells based on anatase TiO₂ hollow spheres/carbon nanotube ³⁷ composite films, J. Power Sources, 196 (2011) 7891-7898.
- ³⁸ [47] C. Karunakaran, G. Abiramasundari, P. Gomathisankar, G. Manikandan, V. Anandi, Preparation and ³⁹ characterization of ZnO–TiO2 nanocomposite for photocatalytic disinfection of bacteria and detoxification of cyanide

⁴⁰ under visible light, Mater. Res. Bull., 46 (2011) 1586-1592.