



DIV-CC-NNN

From Waste to Feedstock: BHET-driven Integration for Closing the Loop in Eco-Friendly Polyurethane Resins

Gabriele Viada^a, Simone Galliano^a, Alberto Menozzi^b, Federica Tammaro^b, Claudia Barolo^{a,c}, Matteo Bonomo^a

^aDepartment of Chemistry, NIS Interdepartmental Centre and INSTM Reference Centre, University of Turin, Via
Giacchino Quarello 15/a, 10135 - Torino, Italy

^b Demak Polymers S.r.l., Corso Lombardia 44, 10099 - Torino, Italy

^c ICxT Interdepartmental Centre, University of Turin, Lungo Dora Siena 100, 10153 - Torino, Italy
gabriele.viada@unito.it

The enormous worldwide employment of single-use plastic materials is leading to ever-increasing waste generation. Therefore, the use of the latter as a feedstock for the production of waste-derived materials has emerged as a hot topic within both the scientific community and the industrial area. However, to accelerate the creation of an effective and reliable market for secondary raw materials, an essential requirement for circular materials is the ease of implementation in current processes and products¹.

In this perspective, we have started to investigate bis(2-hydroxyethyl) terephthalate (BHET), a low molecular weight diol as the main product of the glycolysis of polyethylene terephthalate (PET), as a promising circular component in the formulation of more sustainable ready-to-market polyurethanes². This approach is particularly appealing considering that the end-of-life of a preeminent thermoplastic polymer on a global scale (i.e. PET) would serve as feeding for the most prevalent thermosetting polymer worldwide³ (i.e. PUs), thereby offering an alternative route for closing the loop on a not negligible portion of PET waste.

In this contribution, we explored an innovative approach to implement BHET as a secondary raw material in the formulation of NCO-terminated prepolymer tailored for thermosetting resins. BHET was seamlessly integrated into the prepolymer formulation, removing the need for modifications to the industrial process, and demonstrating outstanding compatibility with other components within the mixture. The impact of BHET concentrations and its relative ratio with polyether and polyester constituents of the prepolymer on the final resins were systematically evaluated, showcasing the feasibility of fine-tuning the physical, chemical, and mechanical properties of polyurethanes while preserving market-level properties. In conclusion, we proved the successful incorporation of a significant amount of BHET (up to 20% w/w) into novel, eco-friendly prepolymers using a solvent-free methodology, without necessitating additional steps in the industrial workflow.

References:

- [1] Bucknall, D.G., *Philos. Trans. R. Soc. A* (2020) 378, 2176.
- [2] Mariotti, N., Viada, G., Galliano, S., Menozzi, A., Tammaro, F., Gianelli, W., Bonomo, M., Barolo, C., *J. Clean. Prod.* (2023) 408, 137161.
- [3] <https://plasticseurope.org/knowledge-hub/plastics-the-facts-2022/>

Acknowledgements:

This research acknowledges support from the Project CH4.0 under the MUR program “Dipartimenti di Eccellenza 2023–2027” (CUP D13C22003520001). GV acknowledges Decreto Ministeriale n. 1061 from MUR for funding the PhD scholarship.