



AperTO - Archivio Istituzionale Open Access dell'Università di Torino

Thermal stability and hardness of Mg-Cu-Au-Y amorphous alloys

This is the author's manuscript					
Original Citation:					
Availability:					
This version is available http://hdl.handle.net/2318/100017 since					
Published version:					
DOI:10.1016/j.jallcom.2006.08.110					
Terms of use:					
Open Access					
Anyone can freely access the full text of works made available as "Open Access". Works made available under a Creative Commons license can be used according to the terms and conditions of said license. Use of all other works requires consent of the right holder (author or publisher) if not exempted from copyright protection by the applicable law.					

(Article begins on next page)



UNIVERSITÀ DEGLI STUDI DI TORINO

This Accepted Author Manuscript (AAM) is copyrighted and published by Elsevier. It is posted here by agreement between Elsevier and the University of Turin. Changes resulting from the publishing process - such as editing, corrections, structural formatting, and other quality control mechanisms - may not be reflected in this version of the text. The definitive version of the text was subsequently published in

M. Baricco, A. Castellero, M. Di Chio, Zs. Kovacs, P. Rizzi, M. Satta, A. Ziggiotti Journal of Alloys and Compounds 434–435 (2007) 183–186 doi:10.1016/j.jallcom.2006.08.110

You may download, copy and otherwise use the AAM for non-commercial purposes provided that your license is limited by the following restrictions:

(1) You may use this AAM for non-commercial purposes only under the terms of the CC-BY-NC-ND license.

(2) The integrity of the work and identification of the author, copyright owner, and publisher must be preserved in any copy.

(3) You must attribute this AAM in the following format: Creative Commons BY-NC-ND license (<u>http://creativecommons.org/licenses/by-nc-nd/4.0/deed.en</u>),

M. Baricco, A. Castellero, M. Di Chio, Zs. Kovacs, P. Rizzi, M. Satta, A. Ziggiotti Journal of Alloys and Compounds 434–435 (2007) 183–186 doi:10.1016/j.jallcom.2006.08.110

Journal of Alloys and Compounds 434–435 (2007) 183–186

Thermal stability and hardness of Mg–Cu–Au–Y amorphous alloys

M. Baricco^{a,*}, A. Castellero^b, M. Di Chio^a, Zs. Kovacs^c, P. Rizzi^a, M. Satta^a, A. Ziggiotti^a

^a Dipartimento di Chimica IFM and NIS, Universit`a di Torino, Via P. Giuria 9, 10125 Torino, Italy

^b Laboratory of Metal Physics and Technology, ETH Zurich, Wolfgang-Pauli Street 10, CH-8093 Zurich, Switzerland

Department of General Physics, E"otv" os Lor`and University, POB 32, H-1518 Budapest, Hungary

Abstract

In this work the effect of Au addition to the GFA of the $Mg_{65}Cu_{25}Y_{10}$ alloy will be discussed. $Mg_{65}Cu_{25}Y_{10}$ and $Mg_{65}Cu_{15}Au_{10}Y_{10}$ amorphous alloys were obtained by rapid solidification. Copper mould casting gave a fully amorphous phase for $Mg_{65}Cu_{25}Y_{10}$, whereas the equilibrium crystalline phases were observed for $Mg_{65}Cu_{15}Au_{10}Y_{10}$. A single eutectic melting reaction was observed for $Mg_{65}Cu_{25}Y_{10}$ but for $Mg_{65}Cu_{15}Au_{10}Y_{10}$ melting is clearly off-eutectic. The presence of an off-eutectic melting of the alloy allows glass formation only by rapid solidification and reduces the glass forming ability. The addition of Au changes the crystallization mechanism of $Mg_{65}Cu_{25}Y_{10}$ amorphous alloy from polymorphic to primary. Two well-separated crystallization peaks were observed for $Mg_{65}Cu_{25}Y_{10}$, whereas for $Mg_{65}Cu_{15}Au_{10}Y_{10}$ the crystallization is more complicated and two overlapped crystallization signals were obtained, followed by a broad exothermal peak at higher temperature. Y-containing $Mg_{2}Cu$ nanocrystals are formed as first crystallization product for both alloys. The Au-containing sample produces also a nanocrystalline AuCu₃ phase. From the indentation tests, a significant increase of hardness was observed in the Au-containing amorphous alloy during crystallization, because of the formation of nanocrystalline phases.

1. Introduction

Mg-based metallic glasses have a general composition $Mg_d(Cu,Ni)_bTM_c(Y,RE)_d$, where TM represents a transition metal and RE is a rare earth (60 < a < 70). The simplest binary Mg–Cu and Mg–Ni (c, d = 0) systems form metallic glasses only by rapid solidification in a narrow composition range around the eutectic between Mg and Mg₂Cu or Mg₂Ni [1]. The addition of Y or RE (d = 10) significantly improve the glass forming abil-ity (GFA) so that bulk metallic glasses (BMG) can be prepared by copper mould casting [2]. Glass formation may be further improved by addition of TM like Ag [3] and Zn [4] (c = 10) or by a substitution of Y with a RE [5]. A maximum diameter of 14 mm has been recently reported for a Mg₆₅Cu_{7.5}Ni_{7.5}Zn₅Ag₅Y₅Gd₅ BMG prepared in air [6]. Several parameters have been sug-gested to explain the enhancement of GFA by TM addition in Mg-based alloys, but more experimental work is necessary for a complete understanding.

Mg-based metallic glasses show superior mechanical and wear properties and enhanced corrosion resistance with respect

to conventional light alloys [7]. Mg-based BMGs are characterized by a brittle fracture [8] but an enhancement of plasticity may be obtained by particle dispersion [9]. The precipitation of nanocrystals by partial crystallization may further improve mechanical properties of monolithic BMG [10].

Au-Pb-Sb alloys show an high GFA, so that amorphous millimeter sized droplets can be obtained by drop tube processing

[11]. An amorphous $Au_{80}Cu_{10}Y_{10}$ alloy has been obtained by rapid solidification, showing a crystallization temperature of 685 K, which indicates long-term stability at room temperature for potential applications [12]. So, investigations on the effect of Auaddition on thermal stability and mechanical properties of Mgbased amorphous alloys may contribute to the under-standing of the role of TM on GFA and may extend possible applications for precious metallic glasses.

In this work the effect of Au addition on the GFA and the crystallization mechanism of the $Mg_{65}Cu_{25}Y_{10}$ alloy will be discussed.

2. Experimental

Master alloys were prepared from pure elements by induction melting. Ribbons were prepared by melt spinning. Small ingots (up to 3 mm in diameter) were obtained by injection casting technique into a conical Cu mould. The structure



Fig. 1. X-ray diffraction patterns for Mg₆₅Cu₂₅Y₁₀ alloys: (a) master alloy; (b) asquenched ribbon; (c) as-cast ingot with 3 mm diameter; (d) ribbon annealed up to 543 K in the DSC. Intensity data are reported as a function of scattering vector $s = 4\pi \sin \theta / \lambda$, where θ is the diffraction angle and λ is the X-ray wavelength.

and microstructure of various samples were analysed by X-ray diffraction (XRD) and by a microprobe equipped scanning electron microscopy (SEM/EDS). Thermal stability and thermochemical properties were investigated by differential scanning calorimetry (DSC). Indentation tests were carried out, using a stan-dard Vickers microhardness test, to estimate the mechanical properties.

3. Results and discussion

The XRD patterns of $Mg_{65}Cu_{25}Y_{10}$ and $Mg_{65}Cu_{15}Au_{10}Y_{10}$ (at.%) master alloys are reported in curves a of Figs. 1 and 2, respectively. The ternary alloy shows the presence of Mg₂Cu and Mg2Y phases, together with minor contributions from MgY and unidentified phases. With the addition of Au, Mg2Cu remains as equilibrium phase, together with AuCu3 and AuMg3, but no Ycontaining phases were observed, suggesting a possible dissolution of this element into equilibrium compounds. Rapid solidification produced easily an amorphous phase for both sys-tems, as evidenced by patterns b in Figs. 1 and 2. The asymmetry observed in the amorphous halo of the Au-containing alloy seems to suggest the presence of a nanocrystalline phase embed-ded in the as-quenched amorphous matrix. The reduced GFA due to the Au-addition to the ternary alloy is confirmed by the cop-per mould casting experiments. The results of the XRD analysis of as-cast alloys, reported in patterns c of Figs. 1 and 2, show that a fully amorphous phase was obtained for Mg65Cu25Y10, whereas the equilibrium crystalline phases were observed for Mg65Cu15Au10Y10. For the latter, a significant refinement of the microstructure was produced by copper mould casting, as evidenced by the line broadening of diffraction peaks.

The DSC analysis for crystallization of amorphous ribbons and the melting of the master alloys, obtained at 0.33 K s⁻¹, are reported in Fig. 3. Two well-separated crystallization peaks were observed for Mg65Cu25Y10, followed by a single eutec-



Fig. 2. X-ray diffraction patterns for Mg65Cu15Au10Y10 alloys: (a) master alloy; (b) as-quenched ribbon; (c) as-cast ingot with 3 mm diameter; (d) ribbon annealed up to 593 K in the DSC. Intensity data are reported as a function of scattering vector $s = 4\pi \sin \theta / \lambda$, where θ is the diffraction angle and λ is the X-ray wavelength.

tic melting reaction (curves a). For Mg65Cu15Au10Y10 (curves b) the crystallization is more complicated and two overlapped signals were obtained, followed by a broad exothermal peak at higher temperature. Melting is clearly off-eutectic, as evi-denced by a double endothermic peak. T_g is clearly observed at 439 K for the ternary alloy, whereas it is less evident for the Aucontaining amorphous alloy and it can be easily evidenced only at higher heating rates. A summary of the results obtained from the DSC analysis is reported in Table 1. The first step of crystallization in Mg65Cu25Y10 alloy leads to the formation of a Mg2Cu phase which showed some textures, probably because



Fig. 3. DSC traces for crystallization of amorphous alloys (left) and melting of master alloys (right) for (a) Mg65Cu25Y10 and (b) Mg65Cu15Au10Y10. The heating rate was 0.333 K s^{-1} .

Table 1

Results of the DSC analysis for Mg65Cu ₂₅ Y ₁₀ and Mg65Cu ₁₅ Au ₁₀ Y ₁₀ amorphous alloys obtained at 0.33 K s								
Alloy	$T_{g}(\mathbf{K})$	$T_{\mathbf{X}}\left(\mathbf{K}\right)$	H_{X} (kJ mol 1)	E^{1} (kJ mol ⁻¹)	E^2 (kJ mol ⁻¹)	$T_{\rm m}({\rm K})$	$H_{\rm m}$ (kJ mol 1)	
M. C. V	-		_ `	att	att			
65 25 10	439	492	3.6	150	-	734	8.5	
Mg Cu Au Y								
65 15 10 10		489	2.5			733	4.5	

 $T_{\rm g}$, glass transition temperature; $T_{\rm x}$, onset crystallization temperature; $_{\rm H_{\rm x}}$, enthalpy of first crystallization step; $E_{\rm att}^{-1}$, activation energy for crystallization (first peak); $E_{\rm att}^{-2}$, activation energy for crystallization (second peak); $T_{\rm m}$, onset melting temperature; $_{\rm H_{\rm m}}$, enthalpy of melting.

of surface crystallization, as evidenced in the XRD pattern of an amorphous ribbon annealed up to 543 K in the DSC (Fig. 1, curve d). An annealing of a Mg65Cu15Au10Y10 amorphous ribbon up to 593 K in the DSC (i.e. after the double crystallization peak) leads to the formation of nanostructured Y-containing Mg2Cu and AuCu3 phases, as evidenced by the significant broadening of diffraction peaks shown in Fig. 2, curve d. The broad exother-mic peak observed in the DSC trace at higher temperatures is likely related to a microstructure coarsening and to precipitation of equilibrium AuMg3 phase.

SEM analysis of Mg65Cu25Y10 master alloy showed an eutectic microstructure, confirming the melting behaviour reported in Fig. 3, curve a. No ternary crystalline phases have been reported in structural and thermodynamic databases for the Mg-Cu-Y system, so an equilibrium between binary phases has to be considered. Mg2Cu is the crystal phase with the higher driving force for nucleation from the liquid phase [13]. In fact it remains as residual phase in as-quenched partially amor-phous samples and it is the first observed crystallization product (Fig. 1, curve d). A second equilibrium phase is Mg₂Y, which has been found as first nucleating phase during isothermal crys-tallization at 433 K [14]. Binary Cu-Y compounds (Cu₂Y and Cu₃Y) have been also reported as equilibrium phases [14,15], but they were not observed in the master alloy. In order to describe the crystallization of Mg65Cu25Y10 amorphous alloy, а composition-enthalpy plot is reported in Fig. 4, considering



Fig. 4. Composition–enthalpy plot for the Mg₂Cu–Mg₂Y section of the Mg–Cu–Y system. Reference states are hcp-Mg, fcc-Cu and hcp-Y. Curve a, equilibrium compounds; curve b, amorphous phase; curve c, Y-containing Mg₂Y. Open circles: total enthalpy of crystallization for Mg₆₅Cu₂₅Y₁₀ (Refs. [4,17,18] and this work). Open triangle: partial enthalpy of crystallization for Mg₆₅Cu₂₅Y₁₀ (Refs. [13]). Full circle: enthalpy of amorphous Mg₂Cu (Ref. [16]).

the Mg₂Cu-Mg₂Y section of the ternary system. Enthalpy of equilibrium phases (curve a) have been obtained from the Calphad assessment of binary systems [13], whereas the enthalpy of amorphous Mg₂Cu, which is not available experimentally, was taken from molecular dynamic simulations [16]. In order to estimate the enthalpy of the amorphous ternary alloys, experimental data for the heat of crystallization of Mg65Cu25Y10 amorphous alloy [17,18] have been added to the enthalpy of the crystals mixture (curve b). Considering that the first stage of crystallization corresponds to a polymorphous crystallization of the amorphous alloy into a Y-containing Mg2Cu phase, as already reported in Refs. [17,19], a trend for the enthalpy of Y-dissolution in Mg₂Cu can be estimated (curve c) form the experimental values for the heat released during the first $(-3.6 \text{ kJ mol}^{-1})$ and second (-0.4 kJ)kJ mol⁻¹) step of crystallization. It is clear that a polymor-phic crystallization of Mg65Cu25Y10 amorphous alloy into Ycontaining Mg₂Cu may be kinetically favoured. In this case, no solute redistribution is necessary during crystallization and the composition of the residual amorphous matrix remains nearly constant. The crystallization of Mg65Cu 15Au10Y10 amorphous alloy is more complicated and involves a significant diffusion of components. In fact, during the first stages of crystallization, the successive formation of Y-containing Mg2Cu and AuCu3 phases was observed. The different crystallization mechanism observed for Mg65Cu25Y10 and Mg65Cu15Au10Y10 amorphous alloys is confirmed by the values of the activation energy for crystallization, obtained by the Kissinger method and reported in Table 1. In fact, because of Au-diffusion, Mg65Cu15Au10Y10 amorphous alloy needs a higher activation energy for crystallization with respect to Mg65Cu15Au10Y10.

Vickers hardness was measured on as-quenched and annealed

Mg65Cu25Y10 BMG and Mg65Cu15Au10Y10 amorphous ribbon. The results are reported in Fig. 5 as a function of transformed fraction, as deduced from a progressive integration of the DSC crystallization peaks shown in Fig. 3. From the indentation tests, an initial increase in hardness was observed for both alloys as a consequence of crystallization. Mg65Cu25Y10 BMG shows a maximum hardness of about 370 HV at the early stages of crys-tallization, reaching a final value of about 320 HV the end of the transformation. On the contrary, at Mg65Cu15Au10Y10 displays a progressive increasing of the hardness, up to a final value of about 430 HV for a fully crystalline sample. Both a maximum and a progressive increase of hardness as a function of trans-formed fraction has been observed in Mg-based BMGs [10,20]. The effect of a crystalline phase embedded in the amorphous matrix on hardness is strongly related to the size of crystal par-ticles and to the composition of the residual amorphous matrix [21].



Fig. 5. Hardness of $Mg_{65}Cu_{25}Y_{10}$ and $Mg_{65}Cu_{15}Au_{10}Y_{10}$ amorphous alloys as a function of transformed fraction calculated from integration of first DSC crystallization peak.

In fact, nanosized particles dispersed in the amorphous matrix may interact with shear bands during the deformation, acting either as barrier for propagation and as sites for their nucleation, leading to a microstructure which improve mechanical proper-ties during crystallization, as obtained for

 $Mg_{65}Cu_{15}Au_{10}Y_{10}$ amorphous alloy. On the other hand, the presence of precipi-tates bigger than a typical size for shear bands in amorphous alloys (about 30 nm) has a little effect on plastic deformation of the amorphous matrix and the hardness of the composite can be related to the volume fraction of

intermetallic phases [10], as observed in Mg65Cu25Y10.

4. Conclusions

The effect of Au addition to $Mg_{65}Cu_{25}Y_{10}$ alloy on glass formation was discussed.

Rapid solidification gives an amorphous alloy for both $Mg_{65}Cu_{25}Y_{10}$ and $Mg_{65}Cu_{15}Au_{10}Y_{10}$ alloys, but copper mould casting gave a fully amorphous phase only for $Mg_{65}Cu_{25}Y_{10}$, whereas the equilibrium crystalline phases were observed for $Mg_{65}Cu_{15}Au_{10}Y_{10}$. A single eutectic melting reaction was

observed for $Mg_{65}Cu_{25}Y_{10}$ but for $Mg_{65}Cu_{15}Au_{10}Y_{10}$ melting is clearly off-eutectic, so that the glass forming ability appears strongly reduced. The addition of Au changes the crystallization mechanism of $Mg_{65}Cu_{25}Y_{10}$ amorphous alloy from polymorphic to primary. For both alloys, Y-containing $Mg_{2}Cu$ nanocrystals are formed as first crystallization product.

Because of the formation of nanocrystalline phases, a signif-icant increase of hardness was observed in the Aucontaining amorphous alloy during crystallization.

Acknowledgments

Work performed for COFIN/MIUR 2002030504 004 and for MRTN-CT-2003-504692.

References

- A.T.W. Kempen, H. Nitsche, F. Sommer, E.J. Mittemejer, Metall. Mater. Trans. 33A (2002) 1041.
- [2] N.H. Pryds, Mater. Sci. Eng. A 375–377 (2004) 186.
- [3] E.S. Park, H.G. Kang, W.T. Kim, J. Non-cryst. Solids 279 (2001) 154.
- [4] H. Men, Z.Q. Hu, J. Xu, Scritpa Mater. 46 (2002) 699.
- [5] H. Men, D.H. Kim, J. Mater. Res. 18 (2003) 1502.
- [6] E.S. Park, D.H. Kim, J. Mater. Res. 20 (2005) 1465.
- [7] G. Yuan, C. Qin, A. Inoue, J. Mater. Res. 20 (2005) 394.
- [8] X.K. Xi, D.Q. Zhao, M.X. Pan, W.H. Wang, Y. Wu, J.J. Leeandowski, Phys. Rev. Lett. 94 (2005) 125510.
- [9] Y. Xu, H. Ma, J. Xu, E. Ma, Acta Mater. 53 (2005) 1857.
- [10] U. Wolff, N. Pryds, E. Johnson, J.A. Wert, Acta Mater. 52 (2004) 1989.
- [11] M.C. Lee, J.M. Kendall, W.L. Johnson, J. Appl. Phys. Lett. 40 (1982) 382.
- [12] B.C. Giessen, S.V. Gokhale, K.G. Marchev, US Patent 005593514A (1994).
- [13] D. Kim, B. Lee, N.J. Kim, Scripta Mater. 52 (2005) 969.
- [14] H. Men, W.T. Kim, D.H. Kim, J. Non-cryst. Solids 337 (2004) 29.
- [15] A. Inoue, A. Kato, T. Zhang, S.G. Kim, T. Masumoto, Mater. Trans. JIM 32 (1991) 609.
- [16] N.P. Bailey, J. Schiøtz, K.W. Jacobsen, Phys. Rev. B 69 (2004) 144205.
- [17] B.S. Murty, K. Hono, Mater. Trans. JIM 41 (2000) 1538.
- [18] A. Inoue, T. Nakamura, N. Nishiyama, T. Masumoto, Mater. Trans. JIM 33 (1992) 937.
- [19] J. Zhang, H.F. Zhang, M.X. Quan, Z.Q. Hu, Scripta Mater. 49 (2003) 485.
- [20] Zs. Kovacs, A. Castellero, A.L. Greer, J. Lendvai, M. Baricco, Mater. Sci. Eng. A 387–389 (2004) 1012.
- [21] A.L. Greer, Mater. Sci. Eng. A 304-306 (2001) 68.