

AperTO - Archivio Istituzionale Open Access dell'Università di Torino

**Detecting slow deformation signals preceding dynamic failure:  
a new strategy for the mitigation of natural hazards (SAFER)**

**This is the author's manuscript**

*Original Citation:*

*Availability:*

This version is available <http://hdl.handle.net/2318/153862> since

*Publisher:*

European Geosciences Union

*Terms of use:*

Open Access

Anyone can freely access the full text of works made available as "Open Access". Works made available under a Creative Commons license can be used according to the terms and conditions of said license. Use of all other works requires consent of the right holder (author or publisher) if not exempted from copyright protection by the applicable law.

(Article begins on next page)

# Detecting Slow Deformation Signals Preceding Dynamic Failure: A New Strategy For The Mitigation Of Natural Hazards (SAFER)

Sergio Vinciguerra<sup>1,2,3</sup>, Chiara Colombero<sup>1</sup>, Cesare Comina<sup>1</sup>, Anna Maria Ferrero<sup>1</sup>, Giuseppe Mandrone<sup>1</sup>,  
Gessica Umili<sup>4</sup>, Andrea Fiaschi<sup>5</sup> and Gilberto Saccorotti<sup>6</sup>

<sup>1</sup>Dipartimento di Scienze della Terra, Università degli Studi di Torino, Italy; <sup>2</sup>Department of Geology, University of Leicester, UK; <sup>3</sup>British Geological Survey, UK

<sup>4</sup>Dipartimento di Ingegneria Civile, dell'Ambiente e del Territorio, Università degli Studi di Parma, Italy; <sup>5</sup>Fondazione Prato Ricerche, Prato, Italy; <sup>6</sup>Istituto Nazionale di Geofisica e Vulcanologia, Pisa, Italy

Contacts: [sergiocarmelo.vinciguerra@unito.it](mailto:sergiocarmelo.vinciguerra@unito.it); [chiara.colombero@unito.it](mailto:chiara.colombero@unito.it)

## 1. Introduction and background

Pre-failure monitoring is a major aim in territorial risk assessment and mitigation. Detecting slow deformation signals preceding dynamic failure is a main goal for developing early-warning systems.

We deployed a microseismic network for monitoring a rockfall at Madonna del Sasso (VB, Italy) with the aim to identify the characteristic signs of pre-failure processes. The array consists of 4 triaxial geophones (4.5 Hz).

## 2. The site

Madonna del Sasso site is located in NW Italy (Fig. 1a). It is a granitic cliff (**Granito di Alzo**), with a height of about 200 m (Fig. 1b).




Figure 1. Location (a) and aerial view (b) of the cliff of Madonna del Sasso. The symbols indicate the network nodes positions.

## 3. Geophysical characterization

### Electrical Resistivity Tomography (ERT)

- 72 electrodes with 1 m spacing
- Wenner-Schlumberger and Dipole-Dipole array
- Data inversion with Res2DInv software (Fig. 3)




Figure 3. ERT section (Dipole-Dipole configuration).

### Cross-hole Seismic Tomography

- Borehole impactor source
- Prototype borehole string with 8 three-component geophones (10 Hz)
- Hammer (P and S waves)
- Three-component surface geophones (4.5 Hz)
- Manual picking of the first arrival time for P and S waves
- Dataset inversion with GeoTomCG software (Fig. 4 e Fig. 5)




Figure 4. Planar sketch of the site with the traces of the fracture systems and the seismic survey configuration.





Figure 5. Results of the cross-hole seismic tomography for P waves.

## 4. Microseismic monitoring



First results:

**14 Nov 2013 – 31 Mar 2014**  
Nearly 1500 recorded events (Fig. 7) with different waveforms, duration and frequency content.

Figure 6. Microseismic monitoring network scheme.

From a preliminary analysis and classification, less than 20 events (~1%) seems to have signal properties (Fig. 8) related to micro-fracturing processes inside the rock mass.

Figure 7. Cumulative curve of the events (Nov 2013 – Mar 2014).






Figure 8. Selection of different types of signals. From the top to the bottom: seismogram recorded on channel EW of Station 2, frequency content and spectrogram for different types of events: (a) an earthquake (Northern Italy,  $M_L=3.8$ , 2013-11-21 10:36:49.0 UTC, 44.91N 9.03E; (b) a microseismic event; (c) electrical transients and (d) still unclassified events.

## 5. Conclusions and future work

- Preliminary recorded data indicate the occurrence of microseismic swarms with different spectral contents.
- A small but significant percentage can be related to micro-racking processes inside the rock mass.
- A 3D reconstruction of the cliff will be carried out to obtain a seismic velocity model for the localization of microseismic events.
- Additional geophones and accelerometers provided by SEIS-UK will be installed in the next future.
- Rock physical and mechanical characterization along with rock deformation laboratory experiments will be carried out.



Four main discontinuities (Fig. 2) tend to dislocate the frontal portion of the cliff, involving a volume of about 12,000 m<sup>3</sup>.

Figure 2. Main joint systems projection.