AperTO - Archivio Istituzionale Open Access dell'Università di Torino

Enabling technologies for the rapid dechlorination of polychloroarenes and PCBs

This is the author's manuscript

Original Citation:

Availability:

This version is available <http://hdl.handle.net/2318/143040> since

Terms of use:

Open Access

Anyone can freely access the full text of works made available as "Open Access". Works made available under a Creative Commons license can be used according to the terms and conditions of said license. Use of all other works requires consent of the right holder (author or publisher) if not exempted from copyright protection by the applicable law.

(Article begins on next page)

UNIVERSITÀ DEGLI STUDI DI TORINO

This Accepted Author Manuscript (AAM) is copyrighted and published by Elsevier. It is posted here by agreement between Elsevier and the University of Turin. Changes resulting from the publishing process - such as editing, corrections, structural formatting, and other quality control mechanisms - may not be reflected in this version of the text. The definitive version of the text was subsequently published in [*Chemosphere*, Vol.9, Issue , 2013, DOI: 10.1016/j.chemosphere.2013.03.030].

You may download, copy and otherwise use the AAM for non-commercial purposes provided that your license is limited by the following restrictions:

(1) You may use this AAM for non-commercial purposes only under the terms of the CC-BY-NC-ND license.

(2) The integrity of the work and identification of the author, copyright owner, and publisher must be preserved in any copy.

(3) You must attribute this AAM in the following format: Creative Commons BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/deed.en>), [DOI: 10.1016/j.chemosphere.2013.03.030]

Enabling Technologies for the Rapid Dechlorination of Polychloroarenes and PCBs

Giancarlo Cravotto,^{*†} Davide Garella,[†] Lara Beltramo,[†] Diego Carnaroglio,[†] Stefano Mantegna,[†] and Carlo Maria Roggero.[‡]

[†] Dipartimento di Scienza e Tecnologia del Farmaco, Università di Torino, Via P. Giuria 9, Torino 10125, Italy.

[‡] Sea Marconi Technologies, Via Ungheria 20, 10093 Collegno (TO), Italy.

*E-mail: giancarlo.cravotto@unito.it; Fax: +39 011 6707687; Tel: +39 011 6707684

Abstract

Dielectric heating and acoustic cavitation (ultrasound or high-performance disperser) may all dramatically enhance conversion rates and yields in heterogeneous metal-assisted organic reactions even when low reagent excesses are used. These so called "enabling technologies" bring with them process intensification, safer protocols, cost reduction and energy savings. We herein describe a series of rapid polychlorinated aromatic and PCBs dechlorinations (15 min) carried out in a moderate excess of metallic sodium and using non-conventional techniques. We compared the results with those obtained for reactions carried out under conventional heating and with those performed with less reactive metals such as magnesium and zinc. In this comparison, high-intensity ultrasound stands out as the technique of choice.

KEYWORDS. *Polychloroarenes, PCBs, Dechlorination, Ultrasound, Microwaves, High-performance disperser.*

1. Introduction

Reductive dechlorination has become one of the most attractive topics in chemistry since the Stockholm Convention on Persistent Organic Pollutants (POPs) imposed the elimination of polychlorinated biphenyls (PCBs) use by 2025 and their disposal via environmentally sound waste management by 2028. Besides incineration or high temperature pyrolysis, which are powerful but controversial elimination methods, there are several non-combustion alternatives to be considered. These are reported in Table 1. Of the several dechlorination methods available, the metal based process has been singled out as the most cost effective and efficient because no toxic by-products (i.e. biphenyl, phenylcyclohexadiene, and phenylcyclohexene) are formed. Nevertheless, safety concerns have been voiced over the huge metal excess that is usually required. Alkaline-earth metals (Ca, Mg) and transition metals (Ni, Pd, Fe, Ti and Zn) (Mitoma et al., 2004; Upendra and Suresh, 2008; Azzena et al., 2010; Liu et al., 2009; Zhang et al., 2011; Zhang, 2003; Fuku et al., 2010; Feng and Lim, 2005) have been investigated as alternatives to the alkaline metals (mainly Na) that are normally used. The reaction times of PCB dechlorination are in the region of several hours or even days. The use of alternative energy sources, such as microwaves (MW) (Kappe, 2004), ultrasound (US) (Cravotto and Cintas, 2006) or mechanochemistry (Nasir and Varma, 2012; Stolle

et al., 2011) has been proven to strongly accelerate the reductive process and limit gaseous emissions (Tajik et al., 2012; Liu et al., 2011; Zhang and Hua, 2000; Sáez, 2011).

Table 1. Non-combustion technologies for PCBs degradation.

METHOD	CHARACTERISTICS	Ref.
Reduction with alkali-metals	<ul style="list-style-type: none"> • Metal stability is a crucial factor (i.e. Ca vs Na) • Mild conditions (r.t., N₂ atmosphere) • Improved by catalysts (i.e. Pd/C, TiCl₄, CoCl₂, Ni(OAc)₂) 	Chiu, <i>et al.</i> , 2012; Noma, <i>et al.</i> , 2003.
Base-catalyzed decomposition	<ul style="list-style-type: none"> • Cost-effective and safe dechlorination occurs with alkali hydroxides 	Takada, <i>et al.</i> , 1997; Sun, <i>et al.</i> , 2007; Ye, <i>et al.</i> , 2011.
Catalytic hydro-dechlorination	<ul style="list-style-type: none"> • Heterogeneous catalysts (i.e. Fe, Ni, or Pd) and H₂ pressure • Aqueous or organic solvents • Generation of biphenyls, HCl 	Schüth and Reinhard, 1998.
Photochemical - electrochemical processes	<ul style="list-style-type: none"> • Closed systems, mild and eco-friendly conditions • Safe additives (i.e. 2-propanol) 	Hawarl, <i>et al.</i> , 1992; Noma, <i>et al.</i> , 2002; Ghosh, <i>et al.</i> , 2012.
Plasma arc	<ul style="list-style-type: none"> • High efficiency • Environmentally friendly • Generation of H₂O₂, H₂, O₂, O₃ (also radicals) • Shock waves and UV light may occur simultaneously • Mandatory energy control 	Du, <i>et al.</i> , 2005.
Microbial reductive transformation	<ul style="list-style-type: none"> • Temperature, pH, substrate composition monitoring for microorganisms growth • Slow process 	Borja, <i>et al.</i> , 2005; Field and Sierra-Alvarez, 2008.

The use of metal particles in a MW oven can result in arcing and generate fire or explosion if a flammable solvent is present. It is, however, possible to perform organic reactions using well-dispersed

93 fine metal particles in a high-boiling-point polar solvent. Whittaker
94 and Mingos described all the safety operations needed to minimize
95 the risk of arcing which include moderating the power rating, using
96 low metal loads and ensuring efficient stirring (Whittaker and
97 Mingos, 2000). Kappe showed, for the first time, how the electric
98 field strength could influence the outcome of a chemical reaction. In
99 low field density conditions, the metal undergoes a cleaning effect
100 and becomes more reactive, whereas under a more intense
101 electrostatic discharge the high temperature reached generates a
102 carbonaceous material that covers the metal, thus reducing its
103 effect (Gutmann et al., 2011). Besides the close control of electric
104 field strength, another method that can influence this type of
105 reaction is the use of an inert atmosphere (N_2 or Ar_2 pressure). This
106 provides a totally safe environment in which to carry out the
107 procedure as it avoids the risk of combustion and explosion in all
108 MW reactions that use metals in a pivotal role (Cintas et al., 2012).
109 US has found several applications in metal-assisted reactions
110 (Cintas et al., 2011) and in heterogeneous conditions (Cravotto et
111 al., 2003; Palmisano et al. 2011).

112 High-intensity US induces strong acoustic cavitation and streaming
113 which enable efficient mixing, metal surface activation and particle
114 dispersion to occur (Cravotto and Cintas, 2006). In the present
115 study we intend to show how US, MW and high-performance

disperser favor the rapid metal-assisted dechlorination of polychloroarenes and PCBs.

2. Materials and methods

2.1. Materials

All the chemicals were used as received. 1,3,5-trichlorobenzene (<99%) and hexachlorobenzene were purchased from Fluka Chemika, 2,4-dichlorophenol (99%) and a sodium dispersion 30 wt% in toluene (<0.1mm particles size) were purchased from Acros Organics. Sodium cubes (99.95%), magnesium chips (98%) and Zn powder were purchased from Sigma-Aldrich. PCBs oil: (Askarel by Monsanto) a mixture of Aroclor 1260 70% and trichlorobenzene 30%. The US probe system (21.1 kHz, max power 250 W, Ø = 2.92 cm) with a titanium horn is commercially available from Danacamerini s.a.s. (Turin, Italy). MW-assisted reactions were carried out under pressure in a SynthWAVE by Milestone (Bergamo, Italy). An Ultra Turrax® T 25 Basic by IKA was used as the high-performance disperser.

2.2. Gaschromatography Analysis

a) Polychloroarenes; gaschromatography-mass spectrometry (GC-MS) analyses were performed in a Agilent 6890 gaschromatograph (Agilent Technologies - USA) fitted with a Agilent Network 5973 mass detector using a 30 m long capillary column, an i.d. of 0.25 mm and a film thickness of 0.25 µm.

140 GC conditions were; injection split 1:20, injector temperature
141 250°C, detector temperature 280°C. Gas carrier: helium (1.2
142 mL/min), temperature program; from 70°C (2 min) to 300°C at
143 5°C/min.

144 *b) PCBs; Gaschromatography-electron capture detector (GC-ECD)*
145 analyses were performed in a Agilent 6890 gaschromatograph
146 (Agilent Technologies - USA) fitted with an ECD, using a 50 m long
147 5% phenylpolysiloxane capillary column, i.d of 0.20 mm and film
148 thickness 0.33 µm. Gas carrier; helium (1 mL/min), make-up gas
149 for ECD; argon-methane (5%). ECD temp. 340°C. Splitless injection
150 1 µL. Temperature program: from 120°C (1 min), then 50°C/min up
151 to 200°C (1 min); 5°C/min up to a 270°C; 20°C/min up to 315°C.

152 *2.3. MW under pressure*

153 Aryl halide (0.1 mmol, 1 eq), metallic reagent (15 eq of metal for
154 each Cl atom) and toluene (10 mL) were placed in the reaction
155 vessel. The mixture was irradiated with MW (average power 300 W)
156 at 130°C for the optimized time of 15 min under N₂ pressure (5
157 bar). The solution was filtered on a Celite[®] pad, soaked in ethanol
158 to remove any un-reacted sodium and analyzed by GC-MS.

159 *2.4. US and the high-performance disperser*

160 Aryl halide (0.1 mmol, 1 eq), the metallic reagent (15 eq of metal
161 for each Cl atom) and hexadecane (10 mL) were placed in a three-
162 necked-round-bottomed flask. The mixture, pre-heated in an oil
163 bath at 130°C until the sodium melted, was then sonicated with an

immersion horn (21.1 kHz, 60W) for 15 min. In an alternative procedure, a high-performance disperser probe was inserted into the flask and switched on/off intermittently every minute for a total time of 30 min (15 min high speed mixing and 15 min pause) to avoid super-heating and damage to the Ultra Turrax®. The solution was filtered on a Celite® pad, soaked in ethanol to remove any unreacted sodium and analyzed by GC-MS.

3. Results and discussion

In this paper, enabling technologies have been applied to the dechlorination process with the aim of designing a safe, fast and efficient protocol in the presence of a low alkali-metal excess (≤ 15 eq.). Four different techniques have been applied; MW, US, high-performance disperser (Ultra Turrax®) and simple conductive heating in an oil bath (OB) was used as a conventional method reference. The three main parameters that affect the dechlorination rate were; temperature, mixing efficiency and metal/chlorine atom ratio (scheme 1).

Scheme 1. Reductive dechlorination with non-conventional techniques.

186 In this work, dechlorination reactions were carried out by
187 suspending the reducing metal (mainly Na, 15 eq. for each Cl atom)
188 in toluene or a hexadecane solution containing a polychloroarene.
189 The first set of experiments was conducted with trichlorobenzene,
190 2,4-dichlorophenol and hexachlorobenzene.

191 MW-assisted dechlorination reactions were performed in a closed
192 MW reactor (SynthWAVE - Milestone) under nitrogen pressure (5
193 bar) thus avoiding any possible risk of fire and explosion. The high
194 power density (1.5 kW per 1.5 l) and the efficient cooling system
195 enabled fast volumetric heating and rapid cooling with very sharp
196 temperature ramps.

197 Table 2 reports the results achieved for MW-assisted reactions
198 according to the varying conditions and sodium source (sodium
199 cubes or a dispersion 30 wt% in toluene). In the light of the results
200 obtained in a few preliminary experiments with 10 eq. (entry 5), we
201 decided to proceed with a metal excess of 15 eq. for each Cl atom.
202 Although the reactions proceed well in 30 minutes at 150°C (entries
203 1, 10 and 17), we also investigated milder conditions at the same
204 reaction time. Complete dechlorination was also achieved (entries 2,
205 11 and 18) when the reaction was carried out at 130°C, whilst no
206 reaction occurred within the 30 min period at temperatures below
207 the metal melting point (entries 9, 16 and 23). However, the
208 sodium dispersion showed much higher reactivity than the sodium
209 cubes when the temperature was close to the metal melting point

210 because of its higher particle dispersion (entries 8, 15 and 22). A
 211 temperature of 130°C together with a sodium/chlorine atom ratio of
 212 15 eq. and an average reaction time of 15 min was the best
 213 compromise in the case of MW-promoted reactions. Lower
 214 dechlorination yields were detected working under reflux in an OB
 215 (entry 3, 12 and 19).

216

217 **Table 2.** Residual polychloroarenes after MW-promoted
 218 dechlorination with Na (15 eq.) in toluene (5 bar N₂ pressure).

219

Entry	Substrate [#]	Time (min)	Temperature (°C)	Na cubes (residual %)	Na dispersion (residual %)
1		30	150	0	0
2		30	130	0	0
3		30	OB reflux	67	60
5		30	130	14*	10*
6		15	130	0	0
7		7	130	55	54
8		30	100	80	0
9		30	80	100	100
10		30	150	0	0
11		30	130	0	0
12		30	OB reflux	52	44
13		15	130	0	0
14		7	130	13	17
15		30	100	33	0
16		30	80	100	100
17		30	150	0	0
18		30	130	0	0
19		30	OB reflux	100	96
20		15	130	0	0
21		7	130	85	56
22		30	100	100	78
23		30	80	100	100

220 [#] In the cases of incomplete conversion, GC-MS analysis did not detect partially
 221 dechlorinated compounds; results are the mean of at least 2-3 trials

222 * Na 10 eq.

223

224 The optimization of the MW-assisted procedure caused a decrease
225 in reaction time to 15 (entries 6, 13 and 20) and 7 min (entries 7,
226 14 and 21), where the former is the preferred choice. This study
227 has provided us with the following order of reactivity; 2,4-
228 dichlorophenol >> 1,3,5-trichlorobenzene > hexachlorobenzene.
229 The last in the list was the most refractory towards dechlorination.
230 The MW-assisted procedure was employed in experiments carried
231 out with US (average power of 80 W) and with high-performance
232 dispersers (Ultra Turrax® at 10,000 rpm). Both methods generate
233 cavitation phenomena and cause the reactive metal to be very finely
234 dispersed. Moreover they played a pivotal role in the set up of this
235 protocol ensuring the process was strongly accelerated. Since the
236 experiments were carried out at atmospheric pressure and at
237 130°C, toluene was replaced with hexadecane. A constant
238 hexadecane solution reaction temperature was guaranteed by a
239 thermostatted bath (130°C). At this temperature, the metallic
240 sodium (cubes) melted (97.7°C) and therefore easily dispersed into
241 the medium, however, particle size was a crucial point for the other
242 metals (zinc and magnesium). Melting proceeded even more quickly
243 when a commercially available sodium dispersion was used (30 wt%
244 in toluene, < 0.1mm particles size). Table 3 shows the results
245 achieved with the sodium dispersion, zinc and magnesium. The
246 sodium dispersion gave excellent yields, confirming the results

obtained with the MW protocol. The yields were significantly lower in the presence of magnesium and zinc as they act in the solid phase.

Table 3. Residual polychloroarenes after treatment with US or a high-performance disperser with various metals (15 eq.) in hexadecane for 15 min at 130°C.

Entry	Method [#]	Substrate	Residual %		
			Na dispersion	Mg	Zn
24	US	trichlorobenzene	0	91	92
25		2,4-dichlorophenol	0	83	76
26		hexachlorobenzene	0	100	100
27	*Ultra Turrax [®]	trichlorobenzene	0	92	95
28		2,4-dichlorophenol	4	90	88
29		hexachlorobenzene	10	100	100

[#] Results are the mean of 2-3 trials

* Alternatively on/off 1 min (15 min high speed mixing and 15 min pause).

The optimized procedures; MW carried out in a pressurized reactor, high-intensity US with an immersion horn and the high-performance disperser (Ultra Turrax[®] at 10,000 rpm) were also tested in the dechlorination of PCBs. A mineral oil containing 271 ppm of PCBs was used to this aim and was treated with a sodium dispersion at 130°C for 15 min with all techniques. After a few preliminary experiments we defined a sodium excess value of 40 mole eq. as being optimal. Table 4 summarizes the results achieved; 7 ppm with MW, <2 ppm with US, 28 ppm with Ultra Turrax[®], whilst the reference reaction in an oil bath gave a 120 ppm residue. All the reactions were monitored via GC-ECD.

Table 4. Residual PCBs in mineral oil (271 ppm) under OB, Ultra Turrax®, MW and US.

Entry	Method	Time (min)	PCBs residual (ppm) Na (15 mole eq)	PCBs residual (ppm) Na (40 mole eq)
30	oil bath	60	270	120
31	*Ultra Turrax®	15	79	28
32	MW	15	56	7
33	US	15	48	<2

*alternatively on/off 1 min (15 min high speed mixing and 15 min pause).

4. Conclusion

In conclusion, we have herein reported a dechlorination protocol performed under non-conventional techniques that enables a moderate excess of metallic sodium to be used rather than the much higher excesses that are currently commonplace. On the basis of the three main parameters studied, temperature, metal/chlorine ratio and physical activation, we can conclude that the crucial issues in the effectiveness of the procedure are the use of melted metal, a reasonable sodium excess and efficient physical metal activation/dispersion. Rapid reactions in low metal excesses (15 mole eq and 40 eq. for PCBs) are possible thanks to the enabling technologies we have outlined above and would be impossible under conventional heating.

Acknowledgement

Financial support from MAPSYN (grant 309376 - NMP.2012.3.0-1) "Highly efficient syntheses using alternative energy forms" is gratefully acknowledged.

292 **References**

- 293 Mitoma, Y., Uda, T., Egashira, N., 2004. Approach to highly efficient
294 dechlorination of PCDDs, PCDFs, and coplanar PCBs using metallic
295 calcium in ethanol under atmospheric pressure at room
296 temperature. *Environ. Sci. Technol.* 38, 1216-1220.
- 297 Upendra, D., Suresh, S., 2008. Effects of solvent, pH, salts and
298 resin fatty acids on the dechlorination of pentachlorophenol using
299 magnesium–silver and magnesium–palladium bimetallic systems.
300 *J. Hazard. Mater.* 156, 308-316.
- 301 Azzena, U., Dettori, G., Mocci, S., Pisano, L., Cerioni, G., Mocci, F.,
302 2010. Active-sodium-promoted reductive cleavage of halogenated
303 benzoic acids. *Tetrahedron* 66, 9171-9174.
- 304 Liu, G.-B., Masashi, T., Thiemann, T., 2009. A facile method for the
305 dechlorination of mono- and dichlorobiphenyls using Raney Ni–Al
306 alloy in dilute aqueous solutions of alkali hydroxides or alkali
307 metal carbonates. *Tetrahedron* 65, 2497-2505.
- 308 Zhang, C., Li, X., Sun, H., 2011. Palladium-catalyzed
309 hydrodechlorination of aryl chlorides and its mechanism. *Inorg.*
310 *Chim. Acta* 365, 133-136.
- 311 Zhang, W.-X., 2003. Nanoscale iron particles for environmental
312 remediation: An overview. *J. Nanopart. Res.* 5, 323-332.
- 313 Fuku, K., Hashimoto, K., Kominami, H., 2010. Photocatalytic
314 reductive dechlorination of chlorobenzene to benzene in 2-
315 propanol suspension of metal-loaded titanium(IV) oxide

316 nanocrystals in the presence of dissolved sodium hydroxide.
317 Chem. Commun. 46, 5118-5120.

318 Feng, J., Lim, T.T., 2005. Pathways and kinetics of carbon
319 tetrachloride and chloroform reductions by nano-scale Fe and
320 Fe/Ni particles: comparison with commercial micro-scale Fe and
321 Zn. Chemosphere 59, 1267-1277.

322 Kappe, C.O., 2004. Controlled microwave heating in modern organic
323 synthesis. Angew. Chem. Int. Ed. 43, 6250-6284.

324 Cravotto, G., Cintas, P., 2006. Power ultrasound in organic
325 synthesis: moving cavitation chemistry from academia to
326 innovative and large-scale applications. Chem. Soc. Rev. 35, 180-
327 196.

328 Nasir Baig, R.B., Rajender Varma, S., 2012. Alternative energy
329 input: mechanochemical, microwave and ultrasound-assisted
330 organic synthesis. Chem. Soc. Rev. 41, 1559-1584.

331 Stolle, A., Szuppa, T., Leonhardt, S.E.S., Ondruschka, B., 2011. Ball
332 milling in organic synthesis: solutions and challenges. Chem. Soc.
333 Rev. 40, 2317-2329.

334 Tajik, R., Mohabadi, H.A., Khavanin, A., Joneidi, A., Eshreti, B.,
335 Solimanian, A., 2012. Decomposition of PCBs(transformer oil) by
336 microwave radiation in presence of solvent and H₂O₂/TiO₂ agents.
337 Adv. Environ. Biol. 6 (8), 2218-2225.

338 Liu, X., Zhao, W., Sun, K., Zhang, G., Zhao, Y., 2011.
339 Dechlorination of PCBs in the simulative transformer oil by

340 microwave-hydrothermal reaction with zero-valent iron involved.
341 Chemosphere 82 (5), 773-777.

342 Zhang, G., Hua, I., 2000. Cavitation chemistry of polychlorinated
343 biphenyls: Decomposition mechanisms and rates. Environ. Sci.
344 Technol. 34 (8), 1529-1534.

345 Sáez, V. , Esclapez, M.D. , Bonete, P., 2011. Sonochemical
346 degradation of perchloroethylene: The influence of ultrasonic
347 variables, and the identification of products. Ultrason. Sonochem.
348 18, 104-113.

349 Wu, B.-Z., Chen, H.-Y., Wang, S.J., Wai, M.C., Liao, W., Chiu, K.,
350 2012. Reductive dechlorination for remediation of polychlorinated
351 biphenyls. Chemosphere 88, 757-768.

352 Noma, Y., Mitsuhashi, Y., Matsuyama, K., Sakai, S., 2007. Pathways
353 and products of the degradation of PCBs by the sodium dispersion
354 method. Chemosphere 68, 861-869.

355 Takada, M., Uchida, R., Taniguchi, S., Hosomi, M., 1997. Chemical
356 dechlorination of PCBs by the base catalyzed decomposition
357 process, Organohalogen. Compd. 31, 435-440.

358 Sun, Z., Takahashi, F., Odaka, Y., Fukushi, K., Oshima, Y.,
359 Yamamoto, K., 2007. Effects of potassium alkalis and sodium
360 alkalis on the dechlorination of *o*-chlorophenol in supercritical
361 water. Chemosphere 66, 151-157.

362 Ye, X., Jianguo, J., Yong, Y., Guolong, G., 2011. Base-catalyzed
363 destruction of hexachlorobenzene with zero-valent iron. Chem.
364 Eng. J. 173, 415-421.

365 Schüth, C., Reinhard, M., 1998. Hydrodechlorination and
366 hydrogenation of aromatic compounds over palladium on alumina
367 in hydrogen-saturated water. App. Catal., B 18, 215-221.

368 Hawarl, J., Demeter, A., Samson, R., 1992. Sensitized photolysis of
369 polychlorobiphenyls in alkaline 2-Propanol: Dechlorination of
370 Aroclor 1254 in soil samples by solar radiation. Environ. Sci.
371 Technol. 26, 2022-2027.

372 Noma, Y., Muramatu, T., Nishizawa, K., Ohno, M., Sakai, S., 2002.
373 Dechlorination pathways of PCBs by photochemical reaction and
374 catalytic hydrodechlorination. Organohalogen. Compd. 56, 413-
375 416.

376 Ghosh, J.P., Achari, G., Langford, C.H., 2012. Reductive
377 dechlorination of PCBs using photocatalyzed UV light. CLEAN 40,
378 (5), 455-460.

379 Du, C.M., Yan, J.H., Cheron, B.G., 2005. Degradation of 4-
380 chlorophenol using a gas-liquid gliding arc discharge plasma
381 reactor. Plasma Chem. Plasma Process. 27, 635-646.

382 Borja, J., Taleon, D.M., Auresenia, J., Gallardo, S., 2005.
383 Polychlorinated biphenyls and their biodegradation. Process
384 Biochem. 40, 1999-2013.

385 Field, J.A., Sierra-Alvarez, R., 2008. Microbial transformation and
386 degradation of polychlorinated biphenyls. *Environ. Pollut.* 155, 1-
387 12.

388 Whittaker, A.G., Mingos, D.M.P., 2000. Arcing and other microwave
389 characteristics of metal powders in liquid systems. *J. Chem. Soc.*
390 *Dalton Trans.*, 1521-1526.

391 Gutmann, B., Schwan, A.M., Reichart, B., Gspan, C., Hofer, F.,
392 Kappe, C.O., 2011. Activation and deactivation of a chemical
393 transformation by an electromagnetic field: evidence for specific
394 microwave effects in the formation of grignard reagents. *Angew.*
395 *Chem. Int. Ed.* 50, 7636-7640.

396 Cintas, P., Carnaroglio, D., Rinaldi, L., Cravotto, G., 2012.
397 Complementary and synergic effects of microwaves and
398 ultrasound in metal-assisted synthesis. *Chemistry Today* 30, 33-
399 35.

400 Cintas, P., Palmisano, G., Cravotto, G., 2011. Power ultrasound in
401 metal-assisted synthesis: from classical Barbier-like reactions to
402 Click Chemistry. *Ultrason. Sonochem.* 18, 836-841.

403 Cravotto, G., Nano, G.M., Palmisano, G., Tagliapietra, S., Demetri,
404 A., Penoni, A., 2003. The aldol reaction under high intensity
405 ultrasounds: a novel approach to an old reaction. *Eur. J. Org.*
406 *Chem.* 22, 4438-4444.

407 Palmisano, G., Tibiletti, F., Penoni, A., Colombo, F., Tollari, S.,
408 Garella, D., Tagliapietra, S., Cravotto, G., 2011. Ultrasound-

409 enhanced one-pot synthesis of 3-(Het)arylmethyl-4-
410 hydroxycoumarins in water. Ultrason. Sonochem. 18, 652-660.